

Kanlux

AREAS OF APPLICATION

- ▶ OFFICES ▶ ILLUMINATING OF SHOPS
- ▶ WAREHOUSES ▶ UNDERGROUND PARKING
- ▶ PUBLIC BUILDINGS
- ▶ SOCIAL AND TECHNICAL ROOMS

Kanlux

T8 LED TUBES

new IQ-LED EX T8

index	article	power	luminous flux	EEi	Length
35254	IQ-LED EX T8 12W-NW	12W	2520lm	A ↑ G	1212mm
35255	IQ-LED EX T8 12W-CW	12W	2520lm		

new T8 LED GLASSv5

index	article	power	luminous flux	EEi	Length
33216	T8 LED GLASSv5 12W-NW	12W	2220lm	A ↑ G	1212mm
33217	T8 LED GLASSv5 12W-CW	12W	2220lm		

T8 LED GLASSv4

index	article	power	luminous flux	EEi	Length	
33210	T8 LED GLASSv4 9W-NW	9W	1440lm	A ↑ G	602mm	
33211	T8 LED GLASSv4 9W-CW	9W	1440lm			
33212	T8 LED GLASSv4 18W-NW	18W	2880lm		C	1212mm
33213	T8 LED GLASSv4 18W-CW	18W	2880lm			
33214	T8 LED GLASSv4 24W-NW	24W	3840lm		1512mm	
33215	T8 LED GLASSv4 24W-CW	24W	3840lm			

T8 LED GLASSv3

index	article	power	luminous flux	EEi	Length	
26062	T8 LED GLASSv3 9W-NW	9W	1260lm	A ↑ G	600mm	
26063	T8 LED GLASSv3 9W-CW	9W	1260lm			
26064	T8 LED GLASSv3 18W-NW	18W	2520lm		D	1210mm
26065	T8 LED GLASSv3 18W-CW	18W	2520lm			
26068	T8 LED GLASSv3T 18W-NW	18W	2610lm			
26058	T8 LED GLASSv3 22W-NW	22W	3080lm	1512mm		
26059	T8 LED GLASSv3 22W-CW	22W	3080lm			

T8 N LED

index	article	power	luminous flux	EEi	Length	
31194	T8 N LED 9W-NW	9W	1000lm	A ↑ G	602mm	
31193	T8 N LED 9W-CW	9W	1000lm			
31190	T8 N LED 18W-CW	18W	2000lm		E	1212mm
31191	T8 N LED 18W-NW	18W	2000lm			
31192	T8 N LED 22W-NW	22W	2420lm			

Colour Temperature: NW 4000K; CW 6500K, rated voltage: 220-240V

kanlux.com

A wide range
for professional
use

T8 LED TUBES



HIGH
PF>0,9



	T8 N LED			T8 LED GLASSv3			T8 LED GLASSv4			T8 LED GLASSv5	IQ-LED EX T8
efficacy	110lm/W			140lm/W			160lm/W			185lm/W	210lm/W
power	9W	18W	22W	9W	18W	22W	9W	18W	24W	12W	12W
luminous flux Φuse [lm]	1000	2000	2420	1260	2520 / wersja T 2610	3080	1440	2880	3840	2220	2520
light colour	NW 4000K, CW 6500K			NW 4000K, CW 6500K			NW 4000K, CW 6500K			NW 4000K, CW 6500K	NW 4000K, CW 6500K
durability	15 000h			25 000h			30 000h			40 000h	50 000h
EELCD											
beam angle	200°			250° / wersja T 120°			220°			200°	200°
PF	>07			>09			>09			>09	>09
ON/ OFF cycles	≥10 000			≥15 000 - 25 000			≥30 000			≥50 000	≥50 000
shade	milk			milk/transparent (only T8 LED GLASSv3T)			milk			milk	milk
*warranty	2 years			2 years			3 years			4 years	5 years



kanlux.com

*Extended warranty is subject to the terms of the warranty statement available on the website.