



product description:

- designed for distribution system with voltage 1000 V
- intended for installation in environments that require IP 66 protection
- made from UV-resistant stable
- integrated knockouts for mounting on base
- perfect sealing of cables and pipes
- integrated O-ring to install cable glands
- intended for direct installation on the surface without having to support with insulating pad
- stainless steel screws for lid installation
- the option to install special terminal block S-KSK 2
- 7x inlets with $\varnothing 20$ mm; 6x $\varnothing 25$ mm; 5x $\varnothing 32$ mm

material - box: PP (halogen-free, Pb-free material)

material - cover: PA (halogen-free, Pb-free material)

color: light gray RAL 7035

self-snuffing: yes, within 30 s

temperature resistance: -25 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

protection types: IP 66

weight: 272 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

KSK 125_KA - plugs and lid screws inserted in the box, each box packed in shrink foil and labelled; 36 pcs of boxes in cardboard

accessories:

- terminal plate S-66; S-96; SP-96
- terminal plate S-KSK-2
- screwless terminal plates TYP015, TYP016, TYP017, TYP018
- support trunking TS35