



2325 G3 LED

Planar LED downlight

- Multilumen and Multicolor
- Low overall height
- Flexible mounting

The 2325 LED G3 downlight is the perfect option for lighting refurbishments due to its versatility and flexibility. Multilumen technology provides three luminaire luminous fluxes and Multicolour offers a choice of light colours in one luminaire. With refurbishment rings it is suitable for most ceiling openings. The 2325 LED is ideal for reception areas, hotels, restaurants, sales areas, meeting and recreation rooms as well as corridors. With this you master the job!

Why you'll get the job done with the 2325 G3 LED downlight

- NEW: Multilumen and Multicolour: Adjustable luminous flux (2,000 lm, 1,400 lm, 800 lm) and light colors (3,000 K, 4,000 K)
- NEW: With refurbishment rings suitable for ceiling openings from 150 mm to 250 mm
- Toolless ceiling installation due to quick mounting springs
- Very low recess depth (43 mm incl. control gear unit)
- Pleasant light effect due to uniform illumination
- High efficiency (up to 105 lm/W) and reliable service life (50,000 h, L65).

2325 G3 LED at a glance

Dimensions:	Ø 170 x 43 mm; Ø 230 x 43 mm
Luminaire luminous flux:	1.800 lm, 1.000 lm (Multilumen)
Colour temperature:	3.000 K, 4.000 K
Connected load:	19 W, 13 W, 7 W
Protection class:	IP20 / IP44 (on room side) / IK02
Safety class:	II
Weight:	0,4 kg 0,5 kg

All versions of 2325 G3 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
Multi-colour / multi-lumen (light colour and luminous flux adjustable)						
2325 G3 C05 OA LED 20/14/08/ML-8MC ET	7791140	2000 / 1400 / 800	19 / 13 / 8	3000 / 4000	Ø 170 x 43 mm	1 x 13 TC-TEL / 1 x 18 TC-TEL 1 x 26 TC-TEL / 1 x 32 TC-TEL 2 x 13 TC-TEL / 2 x 18 TC-TEL
2325 G3 C07 OA LED 20/14/08/ML-8MC ET	7791240	2000 / 1400 / 800	19 / 13 / 8	3000 / 4000	Ø 230 x 43 mm	1 x 13 TC-TEL / 1 x 18 TC-TEL 1 x 26 TC-TEL / 1 x 32 TC-TEL 2 x 13 TC-TEL / 2 x 18 TC-TEL

Parts for 2325 G3 LED

Product reference	TOC	Description	Colour	Dimensions L x W x H [mm]	Weight
2325 G3 C05 SP 200	8120600	Mounting accessories / refurbishment ring for ceiling cutouts Ø 150 - 200 mm.	White	Ø 215 x 11	0,1 kg
2325 G3 C07 SP 250	8120500	Mounting accessories / refurbishment ring for ceiling cutouts Ø 200 - 250 mm.	White	Ø 275 x 11	0,1 kg