



Softone

Softone 18W WW E27 220-240V 1PF/6

Extremely compact covered energy-saving lamp that produces soft white light

Product data

General Information		
General information		
Cap base	E27 [E27]	
Nominal lifetime (nom.)	10000 h	
Switching cycle	30000X	
Light Technical		
Colour code	827 [CCT of 2,700 K]	
Luminous flux (nom.)	1050 lm	
Luminous flux (rated) (nom.)	1050 lm	
Colour designation	Warm white (WW)	
Lumen maintenance 2,000 hours (nom.)	83 %	
Chromaticity coordinate X (nom.)	463	
Chromaticity coordinate Y (nom.)	420	
Correlated colour temperature (nom.)	2700 K	
Luminous efficacy (rated) (nom.)	55 lm/W	
Color rendering index (min.)	81	
Color rendering index (nom.)	82	
LLMF at end of nominal lifetime (nom.)	65 %	
Operating and Electrical		
Input frequency	50 or 60 Hz	
Power (Rated) (Nom)	18.0 W	
Lamp current (nom.)	140 mA	
Starting time (nom.)	1.0 s	
Warm-up time to 60% light (min.)	10 s	

Warm-up time to 60% light (max.)	100 s
Power factor (nom.)	0.6
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	no
Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (max.)	2.0 mg
Mercury (Hg) content (nom.)	1.5 mg
Energy Consumption kWh/1000 h	18 kWh
Product Data	
Full product code	871829168278300
Order product name	Softone 18W WW E27 220-240V 1PF/6
EAN/UPC – product	8718291682783
Order code	68278300
Numerator – quantity per pack	1
Numerator – packs per outer box	6
Material no. (12NC)	929689118902
Net weight (piece)	0.101 kg


Datasheet, 2018, September 5 data subject to change

Softone

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Dimensional drawing



Ambiance 18W WW E27 220-240V 50/60Hz

Product	D (max)	C (max)	F (max)
Softone 18W WW E27 220-240V 1PF/6	71.0 mm	137.0 mm	47.3 mm

