



MASTER TL5 High Output



MASTER TL5 HO 24W/865 SLV/40

This TL5 lamp (tube diameter 16 mm) offers high light output. The TL5 HO lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


| General information | | | |
|------------------------------------|----------------------|--|---------------|
| Cap-Base | G5 [G5] | Luminous Flux (Rated) (Nom) | 1575 lm |
| Life to 50% Failures Preheat (Nom) | 30000 h | Color Designation | Cool Daylight |
| Features | na [Not Applicable] | Luminous Efficacy (@ Max Lumen, Rated) (Nom) | 81 lm/W |
| System Description | High Output | Chromaticity Coordinate X (Nom) | 0.313 |
| LSF Preheat 2000 h Rated | 99 % | Chromaticity Coordinate Y (Nom) | 0.337 |
| LSF Preheat 4000 h Rated | 99 % | Correlated Color Temperature (Nom) | 6500 K |
| LSF Preheat 6000 h Rated | 99 % | Luminous Efficacy (rated) (Nom) | 72 lm/W |
| LSF Preheat 8000 h Rated | 99 % | Color Rendering Index (Max) | 85 |
| LSF Preheat 16000 h Rated | 97 % | Color Rendering Index (Min) | 80 |
| LSF Preheat 20000 h Rated | 84 % | Color Rendering Index (Nom) | 82 |
| Flux measurement reference | Sphere | LLMF 2000 h Rated | 96 % |
| | | LLMF 4000 h Rated | 95 % |
| | | LLMF 6000 h Rated | 94 % |
| | | LLMF 8000 h Rated | 93 % |
| | | LLMF 12000 h Rated | 92 % |
| | | LLMF 16000 h Rated | 91 % |
| Light technical | | | |
| Color Code | 865 [CCT of 6500K] | | |
| Luminous Flux (Nom) | 1575 lm | | |

MASTER TL5 High Output

| | |
|---------------------------------|------------------|
| LLMF 20000 h Rated | 90 % |
| Operating and electrical | |
| Power (Nom) | 22.7 W |
| Lamp Current (Nom) | 0.295 A |
| Temperature | |
| Design Temperature (Nom) | 35 °C |
| Controls and dimming | |
| Dimmable | Yes |
| Mechanical and housing | |
| Cap-Base Information | Green Plate |
| Bulb Shape | T5 [16 mm (T5)] |
| Approval and application | |
| Energy Efficiency Class | G |

| | |
|---------------------------------|------------------------------|
| Mercury (Hg) Content (Nom) | 1.2 mg |
| Energy Consumption kWh/1000 h | 23 kWh |
| EPREL Registration Number | 423556 |
| Product data | |
| Full product code | 871150064393355 |
| Order product name | MASTER TL5 HO 24W/865 SLV/40 |
| EAN/UPC - Product | 8711500643933 |
| Order code | 927928086555 |
| Numerator - Quantity Per Pack | 1 |
| Local code description | MASTER TL5 HO 24W/865 SLV/40 |
| Numerator - Packs per outer box | 40 |
| Material Nr. (12NC) | 927928086555 |
| Net Weight (Piece) | 52.000 g |
| ILCOS Code | FDH-24/65/1B-L/P-G5-16/550 |


Dimensional drawing




| Product | D (max) | A (max) | B (max) | B (min) | C (max) |
|------------------------------|---------|----------|----------|----------|----------|
| MASTER TL5 HO 24W/865 SLV/40 | 17 mm | 549.0 mm | 556.1 mm | 553.7 mm | 563.2 mm |

MASTER TL5 HO 24W/865 SLV/40

Photometric data



LDPB_TL5-HO8_865-Spectral power distribution B/W



LDPO_TL5-HO8_865-Spectral power distribution Colour

MASTER TL5 High Output

Lifetime



LDLE_TL5-HO8_0001-Life expectancy diagram

LDLE_TL5-HO8_0002-Life expectancy diagram



LDLM_TL5-HO8_0001-Lumen maintenance diagram

