



MASTER LED candles and lusters

MASTER LEDcandle DT 6-40W E14 B38 CL

Delivering incandescent-like sparkling light effects, MASTER LED candles and lusters are ideal for general and decorative lighting in the hospitality industry as well as in home environments. Mounted in full view in chandeliers, wall scones or modern luminaires, the clear or frosted glass candles and lusters fit all existing fixtures with an E14, B15, B22 or E27 socket, and enhance the aesthetic appeal of the chandelier or luminaire both when on and off, with their unique, eye-catching lens design. They produce a beautiful sparkling warm light that delivers huge energy savings and minimizes maintenance cost.

Product data

General Information		Operating and Electrical	
Cap-Base	E14 [E14]	Input Frequency	50 to 60 Hz
EU RoHS compliant	Yes	Power (Nom)	6 W
Nominal Lifetime (Nom)	25000 h	Lamp Current (Nom)	35 mA
Switching Cycle	50000X	Wattage Equivalent	40 W
Technical Type	6-40W	Starting Time (Nom)	0.5 s
		Warm Up Time to 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.7
		Voltage (Nom)	220-240 V
Light Technical		Temperature	
Color Code	822-827 [tunable warm white]	T-Case Maximum (Nom)	95 °C
Luminous Flux (Nom)	470 lm		
Color Designation	Warm White (WW)	Controls and Dimming	
Correlated Color Temperature (Nom)	- K	Dimmable	Yes
Luminous Efficacy (rated) (Nom)	75 lm/W		
Color Consistency	<6		
Color Rendering Index (Nom)	80		
LLMF At End Of Nominal Lifetime (Nom)	70 %		

MASTER LED candles and lusters

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	B38

Approval and Application

Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	6 kWh

Product Data

Full product code	871869645350600
-------------------	-----------------

Order product name	MASTER LEDcandle DT 6-40W E14 B38 CL
EAN/UPC - Product	8718696453506
Order code	929001140402
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001140402
Net Weight (Piece)	0.063 kg

Dimensional drawing



Product	D	C
MASTER LEDcandle DT 6-40W E14 B38 CL	38 mm	113 mm

LED DT 6-40W E14 2200-2700K B38 CL

Photometric data

