



## Art.-Nr. P002, P003, P004

- Kein Dosen und Leitungen suchen
- Zeitersparnis durch Schnellmontage
- Putzbündig laut VDE
- Schaltungen fertig verkleben



## Technische Daten

## Sonstige Eigenschaften

Farbe	blau
DIN	EN 60670-1
VDE	0606-1
Norm-Kombinationsabstand	71 mm
Zahnverrastung	Ja
Kombinierbar	Ja
Leitungsübergang	Vollisoliert bei Kombination
Zolltarif-Nr. (P002)	39259080
EAN (P003)	4260182060100
Zolltarif-Nr. (P003)	39259080
EAN (P004)	4260182060094
Zolltarif-Nr. (P004)	40169997

## Abmessungen &amp; Verpackungen

Durchmesser Unterteil	66 mm
Durchmesser Oberteil mit Putzdeckel	64 mm
Tiefe (verstellbar)	58 mm - 75 mm
Ausbrechöffnungen für Leitungen und Rohre	20 mm / 25 mm
Durchmesser Bohrdeckel	68 mm
Randtiefe Bohrdeckel	68 mm
Randtiefe Bohrdeckel	6 mm
Durchmesser Dorn innen	6 mm
Dornlänge Bohrdeckel	30 mm
Querschnitt (1,5 mm)	6 Klemmen, 20 Leiter
Querschnitt (2,5 mm)	5 Klemmen, 15 Leiter



**Order-no.: P002, P003, P004**

- No more searching for cables
- Huge time and cost savings
- Squared up to the plaster according to VDE
- Lock the circuits

Data sheet



## Technical data

### Other characteristics

Colour	blue
DIN	EN 60670-1
VDE	0606-1
Standard combination distance	71 mm
Catch mechanism	yes
Combinable	yes
Power transition	completely insulated (with combination)
EAN (P002)	4260182060070
Customs tariff number (P002)	39259080
EAN (P003)	4260182060100
Customs tariff number (P003)	39259080
EAN (P004)	4260182060094
Customs tariff number (P004)	40169997

### Dimensions & packaging

Diameter lower part	66 mm
Diameter upper part with plaster cover	64 mm
Depth (adjustable)	58 mm - 75 mm
Break-out openings for pipes and tubes	20 mm / 25 mm
Diameter drill cover	68 mm
Border depth drill cover	68 mm
Border depth drill cover	6 mm
Diameter mandrel inside	6 mm
Mandrel length drill cover	30 mm
Cross section (1.5 mm)	6 clamps, 20 conductors
Cross-section (2.5 mm)	5 clamps, 15 conductors