

## General info

## DECORATIVO - Wall

Indoor wall mounted adjustable lamp with multiple sources, in-built switch and diffuse and direct light emission



Ean	8021696158242
Item	NORDIK AP2
Installation	Wall
Guarantee	5 years
Gross weight	1.16 kg
Volume	0.015625 m <sup>3</sup>

## Technical info

Net weight	0.63 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	100-240 V AC 50/60 Hz Integrated switch button
Power supply	In-built, included Replaceable (by qualified operators only), electronic
Adjustability	YES



## Source info

Integrated source	Light bulb (not included), Integrated LED module
Replaceable source	Replaceable (LED: by qualified operators only)
Power	E14/LED max 1 x 40W / 1.5 W
Emission	Diffuse + Direct
Max consumption	max 40W / LED 1.5 W
Features LED	LED SMD BRIDGELUX
CCT	3000 K
Duration LED (t. 25°C)	20000 h
CRI	> 80
Light beam	23°
Light beam flux	100 lm
Useful light flux	LED 80 lm
Photobiological risk	2
Standby power	< 0.50 W
Bulb included	LED INTEGRATO 100lm 3000K -