ideal lux,





General info

Technical - Recessed

Indoor ceiling recessed projector with integrated LED sources and direct light emission

Ean	8021696192345
Item	GAME ROUND 11W 3000K BK GD
Installation	Recessed (Ceiling)
Guarantee	5 years
Gross weight	0.32 kg
Volume	0.00115 m³

Technical info

Net weight Insulation class Protection index Operating temperature

Dimmer

Power output Power supply

Load resistance Front protection index Accessories not included

Recessed specifications

88	
85	

0.28 kg
II
IP20
0° ~ +40 °C
Non-dimmable, On-Off
220-240 V AC 50/60 Hz
Separate, included
YES (by qualified operators only), electronic
Ø 74 - h. ≥ 100 , 3-40
IK06
IP40 [DO NOT COVER]
Dimmable driver

Source info

Integrated source	h
Repleaceable source	Y
Power	1
Emission	D
Max consuption	n
Features LED	L
ССТ	3
Duration LED (t. 25°c)	5
CRI	>
SDCM	5
Light beam	3
UGR Maximum	<
Light beam flux	1
Useful light flux	9
Standby power	<

Integrated LED module	
YES (by qualified operators only)	
11W	
Direct	
max 11,00 W	
LED COB CREE	
3000 K	
50000 h	
> 80	
5	
36°	
< 19	
1100 lm	
940 lm	
< 0.50	