

## General info

## Technical - Recessed


Indoor ceiling recessed projector with integrated LED sources and direct light emission



|                     |                          |
|---------------------|--------------------------|
| <b>Ean</b>          | 8021696244808            |
| <b>Item</b>         | VIRUS FI WH WH           |
| <b>Installation</b> | Recessed (Ceiling, Wall) |
| <b>Guarantee</b>    | 5 years                  |
| <b>Gross weight</b> | 0.08 kg                  |
| <b>Volume</b>       | 0.00027 m <sup>3</sup>   |

## Technical info

|                                |   |
|--------------------------------|---|
| <b>Net weight</b>              | 0.07 kg   |
| <b>Insulation class</b>        | II  |
| <b>Protection index</b>        | IP20  |
| <b>Operating temperature</b>   | 0° ~ +40 °C   |
| <b>Dimmer</b>                  | Non-dimmable, On-Off  |
| <b>Power output</b>            | 220-240 V AC 50/60 Hz   |
| <b>Power supply</b>            | Separate, included<br>YES (by qualified operators only), electronic |
| <b>Recessed specifications</b> | Ø 30 - h. ≥ 60 , 10-30  |



## Source info

|                               |   |
|-------------------------------|---|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | 3W  |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 3 W                                   |
| <b>Features LED</b>           | LED SMD OSRAM                             |
| <b>CCT</b>                    | 3000 K                                    |
| <b>Duration LED (t. 25°C)</b> | 50000 h                                   |
| <b>CRI</b>                    | > 90                                      |
| <b>SDCM</b>                   | -   |
| <b>Light beam</b>             | 20°                                       |
| <b>Light beam flux</b>        | 210 lm                                    |
| <b>Useful light flux</b>      | 170 lm                                    |
| <b>Standby power</b>          | < 0.50                                    |