



## General info

### Technical - Recessed

Indoor ceiling recessed adjustable projector with integrated LED sources and direct light emission

|                     |                          |
|---------------------|--------------------------|
| <b>Ean</b>          | 8021696248165            |
| <b>Item</b>         | NOVA FI 12W 3000K WH     |
| <b>Installation</b> | Recessed (Ceiling, Wall) |
| <b>Guarantee</b>    | 5 years                  |
| <b>Gross weight</b> | 0.62 kg                  |
| <b>Volume</b>       | 0.001563 m <sup>3</sup>  |

## Technical info

|                                 |  |
|---------------------------------|--|
| <b>Net weight</b>               | 0.54 kg  |
| <b>Insulation class</b>         | II   |
| <b>Protection index</b>         | IP20   |
| <b>Compliance</b>               | CE   |
| <b>Operating temperature</b>    | 0° ~ +40 °C  |
| <b>Dimmer</b>                   | Non-dimmable, On-Off   |
| <b>Power output</b>             | 220-240 V AC 50/60 Hz  |
| <b>Power supply</b>             | Separate, included<br>Replaceable (by qualified operators only),<br>electronic |
| <b>Recessed specifications</b>  | Ø 90 - h. ≥ 180 , 3-30   |
| <b>Adjustability</b>            | vert. 0°-90° , orizz. 0°-360°  |
| <b>Accessories not included</b> | Dimmable driver, Narrow beam lens  |

## Source info

|                               |   |
|-------------------------------|---|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | 12 W                                      |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 12 W                                  |
| <b>Features LED</b>           | LED COB PHILIPS                           |
| <b>CCT</b>                    | 3000 K                                    |
| <b>Duration LED (t. 25°C)</b> | 50000 h                                   |
| <b>CRI</b>                    | > 90                                      |
| <b>SDCM</b>                   | -   |
| <b>Light beam</b>             | 38°                                       |
| <b>UGR Maximum</b>            | < 19                                      |
| <b>Light beam flux</b>        | 1000 lm                                   |
| <b>Useful light flux</b>      | 800 lm                                    |
| <b>Standby power</b>          | < 0.50 W                                  |