

## General info

### Outdoor - Wall


Outdoor wall mounted adjustable projector with integrated LED sources and direct light emission



|                     |                         |
|---------------------|-------------------------|
| <b>Ean</b>          | 8021696251011           |
| <b>Item</b>         | FLOOD AP SENSOR 30W BK  |
| <b>Installation</b> | Wall                    |
| <b>Guarantee</b>    | 5 years                 |
| <b>Gross weight</b> | 0.54 kg                 |
| <b>Volume</b>       | 0.002902 m <sup>3</sup> |

## Technical info

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Net weight</b>            | 0.44 kg                              |
| <b>Insulation class</b>      | I                                    |
| <b>Protection index</b>      | IP65                                 |
| <b>Operating temperature</b> | -15° ~ +45 °C                        |
| <b>Dimmer</b>                | Non-dimmable, On-Off                 |
| <b>Power output</b>          | 220-240 V AC 50/60 Hz                |
| <b>Power supply</b>          | In-built, included<br>NO, electronic |
| <b>Load resistance</b>       | IK06                                 |
| <b>Adjustability</b>         | YES                                  |



## Source info

|                               |                       |
|-------------------------------|-----------------------|
| <b>Integrated source</b>      | Integrated LED module |
| <b>Replaceable source</b>     | -                     |
| <b>Power</b>                  | LED 30W               |
| <b>Emission</b>               | Direct                |
| <b>Max consumption</b>        | max 30,00 W           |
| <b>Features LED</b>           | LED SMD               |
| <b>CCT</b>                    | 4000 K                |
| <b>Duration LED (t. 25°C)</b> | 25000 h               |
| <b>CRI</b>                    | > 80                  |
| <b>Light beam</b>             | 100°                  |
| <b>Light beam flux</b>        | 2450 lm               |
| <b>Useful light flux</b>      | 2350 lm               |
| <b>Standby power</b>          | < 0.50                |