

## General info

### Outdoor - Floor


Outdoor ground mounted adjustable bollard with integrated LED sources and direct light emission



<b>Ean</b>	8021696251226
<b>Item</b>	HUB PT H074
<b>Installation</b>	Floor, Ground
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.95 kg
<b>Volume</b>	0.00825 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.72 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP54
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Dimmer</b>	Non-dimmable, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Adjustability</b>	YES



## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	Replaceable (by qualified operators only)
<b>Power</b>	LED 4,5W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 4,50 W
<b>Features LED</b>	LED COB CREE
<b>CCT</b>	3000 K
<b>Duration LED (t. 25°C)</b>	30000 h
<b>CRI</b>	> 80
<b>Light beam</b>	38°
<b>Light beam flux</b>	410 lm
<b>Useful light flux</b>	250 lm
<b>Photobiological risk</b>	1
<b>Standby power</b>	< 0.50 W