ideal lux,



140

140

75

Wire

General info

Outdoor - Recessed lights

Outdoor wall mounted lamp with integrated LED sources and direct asymmetrical light emission

Ean	8021696255514
Item	WIRE 4.0W ANTRACITE
Installation	Wall
Guarantee	5 years
Gross weight	0.53 kg
Volume	0.0018 m ³

Technical info

Net weight	0.46 kg
Insulation class	I
Protection index	IP65
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	Replaceable (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	LED 4 W
Emission	Direct Asymmetrical
Max consuption	max 4,00 W
Features LED	LED SMD
ССТ	3000 K
Duration LED (t. 25°c)	20000 h
CRI	> 80
Light beam flux	200 lm
Useful light flux	70 lm
Standby power	< 0.50 W

IDEAL LUX s.r.l. Via Taglio Destro, 32, 30035 Mirano (Venezia) Tel +39 041 5790500 | Fax +39 041 8872349 | E-mail info@ideal-lux.com www.ideal-lux.com