

## General info

## DECORATIVO - Wall


Indoor wall mounted projector with integrated LED sources, in-built switch and direct light emission



|                     |                         |
|---------------------|-------------------------|
| <b>Ean</b>          | 8021696281001           |
| <b>Item</b>         | PIPE AP NERO            |
| <b>Installation</b> | Wall                    |
| <b>Guarantee</b>    | 5 years                 |
| <b>Gross weight</b> | 0.47 kg                 |
| <b>Volume</b>       | 0.000945 m <sup>3</sup> |

## Technical info

|                              |  |
|------------------------------|--|
| <b>Net weight</b>            | 0.4 kg   |
| <b>Insulation class</b>      | II   |
| <b>Protection index</b>      | IP20   |
| <b>Compliance</b>            | CE   |
| <b>Operating temperature</b> | 0° ~ +40 °C  |
| <b>Dimmer</b>                | Non-dimmable, On-Off   |
| <b>Power output</b>          | 220-240 V AC 50/60 Hz<br>Integrated switch button                              |
| <b>Power supply</b>          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |
| <b>Adjustability</b>         | vert. 0-90°, orizz. 0-320°   |



## Source info

|                               |   |
|-------------------------------|---|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | LED 7 W                                   |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 7 W                                   |
| <b>Features LED</b>           | LED COB CREE                              |
| <b>CCT</b>                    | 3000 K                                    |
| <b>Duration LED (t. 25°c)</b> | 20000 h                                   |
| <b>CRI</b>                    | > 80                                      |
| <b>SDCM</b>                   | 3   |
| <b>Light beam</b>             | 30°                                       |
| <b>Light beam flux</b>        | 580 lm                                    |
| <b>Useful light flux</b>      | 400 lm                                    |
| <b>Photobiological risk</b>   | 1   |
| <b>Standby power</b>          | < 0.50 W                                  |