


## General info

## Outdoor - Floor lamps



|                     |                               |
|---------------------|-------------------------------|
| <b>Ean</b>          | 8021696322599                 |
| <b>Item</b>         | STYLE PT H050 ANTRACITE 4000K |
| <b>Installation</b> | Floor lamps                   |
| <b>Guarantee</b>    | 5 years                       |
| <b>Gross weight</b> | 1.02 kg                       |
| <b>Volume</b>       | 0.012167 m <sup>3</sup>       |

## Technical info

|                              |  |
|------------------------------|--|
| <b>Net weight</b>            | 1.02 kg  |
| <b>Insulation class</b>      | I  |
| <b>Protection index</b>      | IP54   |
| <b>Compliance</b>            | CE   |
| <b>Operating temperature</b> | -15° ~ +45 °C  |
| <b>Dimmer</b>                | NO, On-Off   |
| <b>Power output</b>          | 100-240 V AC 50/60 Hz  |
| <b>Power supply</b>          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                               |                       |
|-------------------------------|-----------------------|
| <b>Integrated source</b>      | Integrated LED module |
| <b>Replaceable source</b>     | No                    |
| <b>Power</b>                  | 9 W                   |
| <b>Emission</b>               | Direct                |
| <b>Max consumption</b>        | max 9,00 W            |
| <b>Features LED</b>           | LED SMD               |
| <b>CCT LED</b>                | 4000 K                |
| <b>Duration LED (t. 25°C)</b> | 30000 h               |
| <b>CRI</b>                    | > 80                  |
| <b>Light beam</b>             | 120°                  |
| <b>Light beam flux</b>        | 1100 lm               |
| <b>Useful light flux</b>      | 830 lm                |